



A patented design curve

A-2

Max. Torque: 1600 Ft. Lbs.

Description	A	B	C	D	E	F	G
A-2 with 1-1/16" hex	.375"	.987"	1.50"	1.55"	5.264"	4.10"	1.125"
A-2 with 1-1/4" hex	.375"	1.096"	1.50"	1.77"	5.264"	4.10"	1.125"
A-2 with 1-7/16" hex	.375"	1.204"	1.50"	1.99"	5.264"	4.10"	1.125"
A-2 with 1-5/8" hex	.375"	1.312"	1.50"	2.20"	5.264"	4.10"	1.125"
A-2 with 1-13/16" hex	.375"	1.420"	1.50"	2.42"	5.264"	4.10"	1.125"
A-2 with 2" hex	.375"	1.529"	1.50"	2.64"	5.264"	4.10"	1.125"
A-2 with 2-3/16" hex	.375"	1.639"	1.50"	2.86"	5.264"	4.10"	1.125"
A-2 with 2-3/8" hex	.375"	1.760"	1.50"	3.10"	5.264"	4.10"	1.125"

A-8

Max. Torque: 7540 Ft. Lbs.

Description	A	B	C	D	E	F	G
A-8 with 2-3/16" hex	.625"	1.94"	2.50"	3.36"	8.78"	6.84"	1.88"
A-8 with 2-3/8" hex	.625"	2.08"	2.50"	3.64"	8.78"	6.84"	1.88"
A-8 with 2-9/16" hex	.625"	2.20"	2.50"	3.86"	8.78"	6.84"	1.88"
A-8 with 2-3/4" hex	.625"	2.34"	2.50"	4.16"	8.78"	6.84"	1.88"
A-8 with 2-15/16" hex	.625"	2.48"	2.50"	4.44"	8.78"	6.84"	1.88"
A-8 with 3-1/8" hex	.625"	2.61"	2.50"	4.70"	8.78"	6.84"	1.88"
A-8 with 3-1/2" hex	.625"	2.75"	2.50"	4.98"	8.78"	6.84"	1.88"
A-8 with 3-7/8" hex	.625"	2.88"	2.50"	5.24"	8.78"	6.84"	1.88"

A-4

Max. Torque: 3860 Ft. Lbs.

Description	A	B	C	D	E	F	G
A-4 with 1-13/16" hex	.50"	1.55"	2.00"	2.68"	7.02"	5.47"	1.50"
A-4 with 2" hex	.50"	1.66"	2.00"	2.90"	7.02"	5.47"	1.50"
A-4 with 2-3/16" hex	.50"	1.76"	2.00"	3.10"	7.02"	5.47"	1.50"
A-4 with 2-3/8" hex	.50"	1.87"	2.00"	3.32"	7.02"	5.47"	1.50"
A-4 with 2-9/16" hex	.50"	1.98"	2.00"	3.54"	7.02"	5.47"	1.50"
A-4 with 2-3/4" hex	.50"	2.09"	2.00"	3.76"	7.02"	5.47"	1.50"
A-4 with 2-15/16" hex	.50"	2.20"	2.00"	3.98"	7.02"	5.47"	1.50"
A-4 with 3-1/8" hex	.50"	2.30"	2.00"	4.18"	7.02"	5.47"	1.50"

For more information or for specific repair needs, Alltite's Customer Support Center has solutions for your immediate problems.